

# sealing machines

## Oliver 1508



Oliver 1508LG Air Operated

The compact and efficient Oliver 1508 sealing machines are available in either a manual version or air operated automatic model. Both machines are designed for use with heat sealable trays, board lids, film lids, and laminated window lids in the Dualpak range of products.

The Oliver 1508 models offer:

- Unique design, providing both a high seal force and a floating hot platten to ensure consistent seal integrity.
- Interchangeable tray carriers to suit Dualpak trays up to DP6100.
- Simplistic operation with the choice of a manual or automatic air operated sealing mechanism.
- Easy to clean stainless steel and anodised aluminium construction, ideal for use in food preparation areas.
- Integrated dual lidding dispenser.
- Compact unit, suitable for limited space applications.
- Suitable only for precut film lidding.
- Adjustable time and temperature controls.



Oliver 1508M Manual Operated



Oliver 1508M Manual Operated

### SPECIFICATIONS:

Dimensions:  
Weight: 22.7kg  
Width: 400mm  
Depth: 650mm  
Height: 349mm  
(plus handle for Manual version)

Electric:  
230 VAC, 4 amps,  
50/60 Hz, single phase.

Air Consumption (Auto version):  
7 bar at 0.1 litres per second.  
Maximum air pressure 10 bar.



Confoil Pty. Ltd. 66 Canterbury Road, Bayswater 3153, Victoria, Australia.  
Ph: +61 3 8720 1966 Fax: +61 3 8720 1988 Email: [info@confoil.com.au](mailto:info@confoil.com.au) Web: [www.confoil.com.au](http://www.confoil.com.au)  
New Zealand: 3 Piermark Dve, Albany Auckland NZ. Ph: 9 415 4580 Fax: 9 415 4510